

# Ecogranite Aquaflow Permeable Block Paving

## Data Sheet



a Forterra brand



Ecogranite Aquaflow permeable blocks are specially designed, incorporating a slot and chamfer, allowing water to disperse at a high rate. Available in 60mm and 80mm rectangular blocks, they sit effortlessly alongside our conventional Ecogranite Royal Forest paving. The textured surface exposes the sparkling granite offering excellent skid/slip resistance. The Ecogranite Aquaflow permeable block can be specified for all sites designed under BS7533-pt13.

**Colours** For an accurate colour match please request a sample.



Cornish Silver Grey



Balmoral



Tintagel †



Truro

**UP TO 77% BY-PRODUCT MATERIAL**

One of the most sustainable paving options currently available.



## Specification

Block sizes (depth)	60mm	80mm
200 x 100mm (blocks per pack)	560	400
Coverage per pack (m <sup>2</sup> )	11.2	8.0
Weight per pack (tonne)	1.47	1.41

Precast concrete block paving  
Manufactured to: BS EN 1338:2003  
Tensile splitting strength 3.6 Mpa  
BBA certificate 97/3373

Abrasion 60mm block Class 3  
Abrasion 80mm block Class 4  
Resistance to weathering Class 3  
Slip/skid resistance Extremely low

**Finishes**  
Bush hammered finish

**Applications**  
60mm thick for use on footpaths,  
domestic drives and 80mm thick  
for use on roads.

The Ecogranite Aquaflow permeable blocks are best used in combination with the Formpave Aquaflow® System, a unique patent protected sub base design which utilises geogrids to reduce sub base depth without effecting structural strength. This system has BBA Accreditation and we offer a free bespoke design service to help you minimise your construction costs.

\* Colour purposes only. † Special order.

**Formpave**

Tufthorn Avenue, Coleford  
Gloucestershire, GL16 8PR

**Tel:** 01594 836 999  
**Fax:** 01594 810 577

**Email:** sales@formpave.co.uk  
**Web:** www.formpave.co.uk